

304 & 316 Stainless Steel Cable Ties

Our cable ties meet most end-users needs, with choices covering a wide range in size & strength. Self-locking mechanism provides maximum strength and durability for securing all sizes of bundles and speeds installation, lowering install cost.

Sharp edges & burrs are removed to protect bundle and make installation easy, fast, accurate & secure. Cable ties are designed to optimize insertion ease and still meet or exceed all applicable strength requirements.

Material: 316 & 304 Grade Stainless Steel

Application: Mass transit, ship building, marine, mining, power stations, petro-chemical off-shore, underground cable laying, solar energy installation and other industrial

Working Temperature: -80°C to +538°C (-112°F to +1000°F)

Colour: Stainless Steel

Features:

- Self-Locking Mechanism for excellent strength & durability
- UV Resistant
- Type 316 excellent for highly corrosive environments
- Fire & chemical resistant
- High loop tensile strength
- Smooth rounded edges suitable for all types of cable insulation
- Non-flammable, water resistant/ no absorption

Item Code (SKU)	Length		Width - mm	Bundle Diameter - mm	Thickness	Tensile Strength	
	Inch	mm				LBS	KGS
CT46X150SS-304	5.9	150	4.5	22	0.25	176	79.8
CT46X200SS-304	7.8	200	4.6	50	0.25	176	79.8
CT46X250SS-304	9.8	250	4.6	65	0.25	176	79.8
CT46X300SS-304	11.8	300	4.6	80	0.25	176	79.8
CT46X350SS-304	13.7	350	4.6	82	0.25	176	79.8
CT46X150SS-316	5.9	100	4.6	22	0.25	176	79.8
CT46X200SS-316	7.8	200	4.6	50	0.25	176	79.8
CT46X250SS-316	9.8	250	4.6	65	0.25	176	79.8
CT46X350SS-316	13.7	350	4.6	82	0.25	176	79.8
CT46X500SS-316	19.6	500	4.6	140	0.25	176	79.8
CT46X750SS-316	29.5	750	4.6	223	0.25	176	79.8
CT46X1100SS-316	43.3	1100	4.6	310	0.25	176	79.8
CT79X200SS-316	7.8	200	7.9	50	0.25	220	99.79
CT79X250SS-316	9.8	250	7.9	65	0.25	220	99.79
CT79X350SS-316	13.8	350	7.9	82	0.25	220	99.79
CT79X500SS-316	19.6	500	7.9	140	0.25	220	99.79
CT79X750SS-316	29.5	750	7.9	223	0.25	220	99.79
CT79X1100SS-316	43.3	1100	7.9	300	0.25	220	99.79

Disclaimer:

All information above is supplied by the manufacturer and to the best of our knowledge is correct & reliable. Customers must decide autonomously about application and end use. Under no circumstances is Cable Ties Australia or its subsidiary companies liable for any damages, indirect or otherwise arising from the sale, resale, transfer, use or mis-use of the product. Liability is limited to the replacement of product deemed to have a manufacturing defect.